

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE DATA RECORD
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u>	<u>AIRPORT ID</u>	<u>PROCEDURE NAME</u>	<u>ORIGINAL/AMENDMENT</u>	<u>CITY</u>	<u>STATE</u>	
SOUTHWEST FLORIDA INTL	KRSW	KRSW RNAV (RF/TF) Rwy 06	Original	FORT MYERS	FL	
<u>AIRPORT ELEVATION</u>	<u>TDZE</u>	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u>	<u>DATED</u>	<u>MAG VAR</u>	<u>EPOCH YEAR</u>
30	N/A	N/A	N/A	N/A	-4.0	2000
<u>FACILITY</u>	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u>	<u>REQUIRED EFFECTIVE DATE</u>			
N/A	N/A	N/A	N/A			

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
SOKIE_	IAF	SOKIE_		IF	FB	1.00	120	0.000	400
SOKIE_	IAF	FEEED_		TF	FB	1.00	120	3.650	3000
FEEED_	IAF	TOUHY_		TF	FB	1.00	99	2.740	2100
TOUHY_	IF	WP08		TF	FB	1.00	58	1.450	1700
WP08	IF	OLASS_		TF	FB	1.00	58	1.943	1100.0
GULLF_	IF	GULLF_		IF	FB	1.00	238	0.000	5000
GULLF_	IF	WP09		TF	FB	1.00	238	2.754	4200
WP09	IF	WP08		RF	FB	1.00	238	7.852	1700
OLASS_	PFAF	KRSW:RW06:AER		TF	FB	0.30	58	3.198	81.6
KRSW:RW06:AER	MAP			CA	FB	1.00	58	0.000	430.0
	MAP	GALVE_		DF	FB	1.00	58	3.700	1000
GALVE_	MAP	RUTHY_		TF	FB	1.00	122	7.508	2300.0
RUTHY_	MAP	CORFU_		TF	FB	1.00	213	6.810	2300.0

MISSED APPROACH

MAP:

1.35 NM from threshold RW06

MISSED APPROACH INSTRUCTIONS:

Climb to 2300 Feet Direct to GALVE_ and via 122 track to RUTHY_ and right turn via 213 track to CORFU_ and hold

ALTERNATE MISSED APPROACH INSTRUCTIONS (DO NOT CHART):

PROFILE:

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.					
3. FAC:	54.1 PFAF	OLASS_ DIST PFAF TO MAP:	1.9	DIST PFAF TO THLD:	3.2
4. MIN ALT:	510				
5. DIST TO THLD FROM PFAF:	3.2	MM: N/A	IM: N/A	150 HAT: N/A	HAT: 1.35
6. MIN GP INCPT:	1100	GP ALT AT PFAF:	MM: N/A	IM: N/A	
7. GP ANGLE:	3	34:1: IS CLEAR	20:1: IS CLEAR	TCH: 55	
8. MSA FROM:	RW06				

AIRPORT
SOUTHWEST FLORIDA INTL

AIRPORT ID
KRSW

PROCEDURE NAME
KRSW RNAV (RF/TF) Rwy 06

ORIGINAL/AMENDMENT
Original

CITY
FORT MYERS

STATE
FL

PBN EQUIPMENT REQUIREMENTS NOTES:

RF Required

NOTES:

Chart: STRKL_: N26° 23' 38.850000000" W81° 48' 52.660000000"
Chart: WINLE_: N26° 24' 52.380000000" W81° 51' 48.260000000"
Procedure Flight Validated IAW FAA AC 90-113A.

ADDITIONAL FLIGHT DATA:

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA

CATEGORY:

<u>FINAL TYPE</u>	<u>DA/MDA</u>	<u>A</u> <u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>B</u> <u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>C</u> <u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>D</u> <u>VIS</u>	<u>HAT/HAA</u>	<u>DA/MDA</u>	<u>E</u> <u>VIS</u>	<u>HAT/HAA</u>
S-RW06	510	1/2	483	510	1/2	483	510	3/4	483	510	1	483			

CHANGES - REASONS:

N/A

COORDINATED WITH:

A4A ALPA AOPA APA HAI NBAA

FLIGHT CHECKED BY

N/A

OFFICE

N/A

DATE

N/A

DEVELOPED BY

Tim Lovell

OFFICE

MITRE PARC NAV WG

DATE

APPROVED BY

Mike Cramer

OFFICE

MITRE PARC WG Lead

DATE

TITLE